

The Abimac logo features the brand name in a stylized, blue, outlined font. Above the letters, there are several curved, blue lines that suggest motion or a field, and a small orange circle is positioned above the 'i'.

News

"Save precious time with AVANTIME!"

BUTTERFLY AVANTIME
ROTARY RAKE

BORELLO®

ROTARY RAKE

BORELLO® BUTTERFLY AVANTIME

The new rake of the Butterfly series combines the well-known advantages offered by the half-carried rake with central swath with a lighter weight and great handiness both at work and during transportation. It is hooked to the front lift three-point linkage of the tractor hitch. Being carried, it demands a tractor able to hoist 1500 kgs.

Working width can be adjusted manually on the extractable arms in order to adapt the rake to the cutting bar width. Ideal to make forage swaths in general, but especially of alfalfa immediately after harvesting to form a soft and perfectly symmetrical swath.

After road transportation the operator does not need to get off the tractor to start working. The machine is ready for use: just release the safety devices of the hydraulic hoisting cylinders from the driver's seat and lower the rotors to start working. The correct working position and machine balance are found by adjusting the height of the tractor hoisting device and the third point position in order to let the teeth pass just over the ground. During the maneuvers at field head just lift both rotors without modifying the height of the hoisting device. You will always obtain homogeneous adjustments. The gearboxes in oil bath are maintenance-free. The axles with four pivoting wheels adapt to the ground very well.



TECHNICAL FEATURES	AVANTIME
• Swath formation	central
• Rotor height adjustment	manual
• Number of gearboxes in oil bath	2
• Rotor diameter	3.00 m each
• Working width with swath	6.00 m - 6.50 m
• Number of extractable fork arms	9 × 2
• Number of forks (spring teeth) per arm	4
• Tractor hitch	front lift
• Number of pivoting wheels each rotor	4 × 15 × 6.00 - 6
• Tandem axles	standard
• Width in transport position	2.50 m
• Total length (transport position)	4.00 m
• Weight with transmission	1150 kg
• Transmission with PTO shaft and fifth wheel	1
• Secondary transmission with PTO shaft and clutch	2
• Required power (starting from)	110/80 Cv/Kw



Manufactured by Abimac s.r.l.
 Reg. Solere, 13 - 12038 Savigliano (CN) - Italy
 tel. ++39 0172 377314 - fax ++39 0172 377288
 info@abimac.it - www.abimac.it

Distributor: